Polypropylene Fibre Rope 3-Strand

Product information



General purpose rope for a variety of marine applications; mooring, towing, fishing, pick-up lines, lifting slings, general purpose use. Resistant to rot, most acids and alkalies. The fibre is UV-stabilized against sunlight.

Standard length: 220m : 4-16mm spool - 18-48mm coil
Specific gravity: 0,91 (floats).
Melting point: Approx. 165°C.
Elongation: Approx. 30%.
Strength wet/dry: 100%.
Shock absorption: Very good.
Water absorption: None.
Abrasion resistance: Good.

... *Read more*

Features: Spliced fibre.
Material: Polypropylene.
Marking: According to standard
Finish: Orange. Other colours possible on request.
Standard: EN ISO 1346

CERTEX Danmark A/S
info@certex.dk
+45 74 54 14 37

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Polypropylene Fibre Rope 3-Strand

Technical data

Part code	Diameter mm	Length m	MBL kN	Rope ends	Weight kg/220m
300300602200130	6	220	5.4	Plain ends	3.7
300300802200130	8	220	9.4	Plain ends	6.6
300301202200130	12	220	19.9	Plain ends	14.5
300301602200130	16	220	34.3	Plain ends	25.5

CERTEX Danmark A/S
info@certex.dk
+45 74 54 14 37

© November 2026 - All Rights Reserved