

## Ferrule TKH Talurit®



### Product information

The turnback ferrule system is easy to use. It is quick, safe and has proved itself to be totally reliable. The ferrules are thoroughly specified and very well defined for many different wire rope applications.

Conical ferrule with an inspection hole to ensure the short end of the wire rope is correctly positioned after swaging. This hole remains open after swaging, due to the pressing in a die with a blind tap.

The ferrules can be used for fibre core, single layer wire ropes, steel core single layer wire ropes, rotation resistant wire ropes and some spiral strand ropes.

**Material:** Aluminium

**Marking:** According to standard

**Standard:** EN 13411-3

*except size range*

**Note:** See the manufacturer's product data sheet below for guidance on dimension selection.

Part code	Ferrule size mm	Delivery time
120100800200	8	10
120100900200	9	2
120101000200	10	2
120101100200	11	2
120101200200	12	2
120101300200	13	2
120101400200	14	2

120101600200	16	2
120101800200	18	2
120102000200	20	2
120102200200	22	2
120102400200	24	2
120102600200	26	2
120102800200	28	2
120103000200	30	2
120103200200	32	2
120103400200	34	2
120103600200	36	2
120103800200	38	2
120104000200	40	10
120104400200	44	2
120105000200	50	2
120105400200	54	2