Lifting Solutions Group
Axel Johnson International

Inferno® Soft Sling

Product information



The Black Inferno® sling is a heat resistant lifting sling designed for demanding lifting tasks where elevated temperatures and controlled handling are required. Manufactured from high-performance aramid materials, it maintains lifting capability in environments where standard slings would degrade. Its matte black version is suited for entertainment and stage rigging where low visibility is required.

WLL range: 2t – 50t (black version up to 2.5t)
EWL range: 0,5m – 16m

When to choose this product

Best for:

- Lifting operations exposed to heat up to 200°C
- Entertainment, theatre, and stage rigging requiring low visibility

Product benefits

- Aramid construction maintains strength at elevated temperatures up to 200°C
- Soft and lightweight design improves handling and positioning accuracy
- Low D:d ratio supports use with smaller diameter lifting points
- High abrasion resistance extends service life in repeated use
- Matte black finish reduces visual impact in stage and event environments

... *Read more*

Material: 100% Aramid
Marking: According to standard, CE-mark, UKCA-marked
Temperature range: Up to +200°C
Standard: EN 1492-2
except material
Warning: Slings should be protected from edges, friction and abrasion, whether from the load or the lifting appliance. Where reinforcements and protection against damage from edges and/or abrasion is supplied as part of the sling, this should be correctly positioned. It may be necessary to supplement this with additional protection.

Safety factor: 7:1

CERTEX Danmark A/S
info@certex.dk
+45 74 54 14 37

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Inferno® Soft Sling

Technical data

Part code	WLL ton	EWL m	Colour
340500300050110	3	0.5	Yellow
340500300100110	3	1	Yellow
340500300200110	3	2	Yellow
340500300300110	3	3	Yellow
340500300400110	3	4	Yellow
340500300500110	3	5	Yellow
340500500050110	5	0.5	Yellow
340500500100110	5	1	Yellow
340500500200110	5	2	Yellow
340500500300110	5	3	Yellow
340500500400110	5	4	Yellow
340500500500110	5	5	Yellow
340501000050110	10	0.5	Yellow
340501000100110	10	1	Yellow
340501000200110	10	2	Yellow
340501000300110	10	3	Yellow
340501000400110	10	4	Yellow
340501000500110	10	5	Yellow

CERTEX Danmark A/S
info@certex.dk
+45 74 54 14 37

© November 2026 - All Rights Reserved