



## Inferno® Soft Sling

### Product information

#### **Inferno®:** The Heat Resistant Soft Sling

The ultra-heat resistant Inferno® soft sling makes it possible to lift heavy payloads when working under extreme heat conditions. Even when the temperature rises to 200°C, the Inferno® soft sling will maintain strength!

#### **Properties:**

The Inferno® soft sling is made of 100% Aramid and available from 0,5m to 65m, with a WLL up to 100t. Inferno® cover can be manufactured in the color black for WLL up to a maximum of 2.5 tons, while those from 3 tons and above are yellow (the natural color of Aramid fiber).

#### **Features:**

- Maintains its strength up to 200°C(!)
- Easy to position
- Low D:d ratio
- Soft, lightweight, and easy to handle
- Improves workflow
- High abrasion resistance
- Environmentally friendly due to the long lifespan
- Creates safer lifting conditions

#### **Sustainability:**

The Inferno® heat-resistant soft sling jacket is repairable, making it a sustainable option. In case of damage to the jacket, it can be repaired, extending the lifespan of the sling and reducing waste.

**Material:** 100% Aramid

**Marking:** According to standard, CE-marked, UKCA-marked

**Temperature range:** to +200°C

**Standard:** EN 1492-2

*except material*

**Note:** kg/m = kg/EWL

**Warning:** Slings should be protected from edges, friction and abrasion, whether from the load or the lifting appliance. Where reinforcements and protection against damage from edges and/or abrasion is supplied as part of the sling, this should be correctly positioned. It may be necessary to supplement this with additional protection.

**Safety factor:** 7:1

| Part Code       | WLL<br>ton |
|-----------------|------------|
| 34050010XXX0110 | 1          |
| 34050020XXX0110 | 2          |
| 34050030XXX0110 | 3          |
| 34050050XXX0110 | 5          |
| 34050100XXX0110 | 10         |
| 34050200XXX0110 | 20         |
| 34050400XXX0110 | 40         |
| 34050500XXX0110 | 50         |