

Connex Connecting Link Pewag CW

Product information



CW Connex connecting link for pewag connex system.
Load pin and collar CBH are also separately available.
Connecting link for:
Master link - chain, chain - chain, hook - chain.
Only for straight pull.


... [Read more](#)

Material: High duty grade 10.
Marking: According to standard, CE-marked, Pewag or PW, winner or 10, H16, batch code and type.
Temperature range: -40°C up to +380°C.
Finish: Orange powder coated.
Standard: EN 1677-1

Safety factor: 4:1
Grade: 10

Connex Connecting Link Pewag CW

Blueprint



Technical data

Part code	Code	WLL ton	LC kN	EWL	b mm	c mm	d mm	e mm	g mm	s mm	t mm	Weight kg
402200100140	CW 5	1	20	38	34	7	7	38	13	9	12	0.06
402200140140	CW 6	1.4	28	44	39	8	8	44	14	11	13	0.08
402200190140	CW 7	1.9	36	53	46	10	9	53	17	13	16	0.14
402200250140	CW 8	2.5	50	62	55	12	10	62	19	14	20	0.24
402200400140	CW 10	4	80	72	64	15	13	72	24	18	22	0.42
402200670140	CW 13	6.7	134	88	79	20	17	88	28	22	26	0.85
402201000140	CW 16	10	200	112	105	24	24	112	34	29	35	1.9
402201600140	CW 19/20	16	320	126	123	32	25	126	42	35	45	3.1
402201900140	CW 22	19	380	157	148	36	26	157	51	39	46	4.6
402202650140	CW 26	26.5	530	190	175	40	30	190	60	46	49	6.8
402204000140	CW 32	40	800	206	216	47	35	206	80	56	63	11.2