CERTEX | Lifting Solutions Group
Axel Johnson International

Eyebolt

Product information



For a maximum angle of use 90º between the two legs - divide the WLL by two. Stated WLL is at 0º.

... *Read more*

Material: Alloy steel.
Marking: According to standard, CE-mark, WLL, sizes, steel quality, productname, traceable.
Finish: Red painted.
Standard: ISO 3266
Note: Approved for lifting.

Safety factor: 4:1.


CERTEX Danmark A/S
info@certex.dk
+45 74 54 14 37

© November 2026 - All Rights Reserved

CERTEX | Lifting Solutions Group
Axel Johnson International

Eyebolt

Blueprint



Technical data

Part code	WLL ton	Thread	Tightening torque Nm	A mm	B mm	C mm	D mm	E mm	F mm	G mm	L mm	Weight kg
421100040030	0.4	M8	8	19.5	35.5	20	8	6	8	44	24	0.06
421100070030	0.7	M10	16	23	43	21	10	7	10	51	28	0.08
421100100030	1	M12	28	29	53	22	12	8	12	64	40	0.14
421100120030	1.2	M14	54	31.5	59.5	26	14	9	14	72	40	0.2
421100150030	1.5	M16	70	36	64	38	16	10	14	79	51	0.3
421100250030	2.5	M20	135	45.5	77.5	32	20	12	18	95	56	0.5
421100400030	4	M24	230	53	94	38	24	12	20.5	110	67	0.92

CERTEX Danmark A/S
info@certex.dk
+45 74 54 14 37

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Eyebolt

	1	**2**
	0°	**0°**
Size	**Single-leg**	**2-legs**
M8X24	0,4	0,8
M10X28	0,7	1,4
M12X40	1,0	2,0
M14X40	1,2	2,4
M16X51	1,5	3,0
M20X56	2,5	5,0
M24X67	4,0	8,0

CERTEX Danmark A/S
info@certex.dk
+45 74 54 14 37

© November 2026 - All Rights Reserved