

Regular Swivel JE Green Pin® G-7723, Jaw-eye

Product information



The Green Pin® JE Swivel CP is a swivel with jaw-eye end-fittings and a split pin. The swivel is made from high tensile steel and can be used under water.

Galvanization of the Green Pin® JE Swivel CP ensures its long-term durability. It is available in a range with a working load limit from 0.39 up to 20.5 ton.

Certification on request: 2.1, 2.2

Standard: Generally to RR-C-271, Type VII, Class 3.

... [Read more](#)

Material: High tensile steel, quenched and tempered


Marking: CE-marked

Finish: Hot dipped galvanized

Safety factor: 5:1

Regular Swivel JE Green Pin® G-7723, Jaw-eye

Blueprint



Technical data

| Part code | WLL ton | EWL mm | a mm | b mm | c mm | d mm | e mm | f mm | g mm | h mm | i mm | Weight kg |
|--------------|---------|--------|------|------|------|------|------|------|------|------|------|-----------|
| 422500040020 | 0.4 | 67 | 6 | 88 | 32 | 18 | 19 | 22 | 67 | 12 | 6 | 0.09 |
| 422500060020 | 0.6 | 75 | 8 | 99 | 41 | 21 | 25 | 23 | 75 | 13 | 8 | 0.16 |
| 422500110020 | 1.12 | 92 | 10 | 122 | 51 | 24 | 32 | 27 | 92 | 16 | 10 | 0.32 |
| 422500160020 | 1.63 | 114 | 13 | 154 | 64 | 33 | 38 | 33 | 115 | 21 | 13 | 0.57 |
| 422500240020 | 2.4 | 135 | 16 | 184 | 76 | 40 | 45 | 38 | 135 | 26 | 16 | 0.98 |
| 422500330020 | 3.3 | 154 | 19 | 211 | 89 | 45 | 51 | 45 | 154 | 31 | 19 | 1.88 |
| 422500450020 | 4.54 | 178 | 22 | 244 | 102 | 53 | 57 | 52 | 178 | 31 | 23 | 2.43 |
| 422500570020 | 5.7 | 217 | 25 | 297 | 114 | 59 | 64 | 72 | 218 | 47 | 29 | 4.02 |
| 422500820020 | 8.2 | 230 | 32 | 335 | 143 | 68 | 80 | 72 | 240 | 57 | 35 | 7.43 |
| 422502050020 | 20.5 | 364 | 38 | 534 | 198 | 110 | 122 | 116 | 381 | 78 | 51 | 22.1 |