Lifting Solutions Group
Axel Johnson International

Half Coupling Link 8-054

Product information



- Proof Load tested at 2.5 times the WLL with certification for each batch manufactured.
- Fatigue rated to 20,000 cycles at 1.5 times the WLL.
- Magnaflux crack detection is performed 100% on each batch.
- To combine with 8-088N Insulated Blank Swivel

... *Read more*

Material: Quenched and Tempered Alloy Steel.
Marking: According to standard
Temperature range: Tempering temperature minimum 400°C
Standard: EN 1677-1

Safety factor: 4:1
Grade: 8


CERTEX Danmark A/S
info@certex.dk
+45 74 54 14 37

© November 2026 - All Rights Reserved

CERTEX | Lifting Solutions Group
Axel Johnson International

Half Coupling Link 8-054

Blueprint



Technical data

Part code	Chain diameter mm	WLL ton	A mm	D mm	K mm	L mm	Weight kg
401200200140	7-8	2	18	9	22	28	0.1
401200320140	10	3.15	25	11	26	34	0.2
401200530140	13	5.3	30	16	35	45	0.4
401200800140	16	8	36	19	38	50	0.6
401201250140	18-20	12.5	42	22	46	60	1.1

CERTEX Danmark A/S
info@certex.dk
+45 74 54 14 37

© November 2026 - All Rights Reserved