# Stainless Lifting Eye Nut DIN 582

**Product information**



Lifting eye nut for common purposes.
Only approved for lifting as an integrated part of a machine (Machine Directive). For other purposes, the next size WLL must be used.

**User information**
Eyebolts/eyenuts to this standard are intended as permanent attachments on equipment such as motors, control cabinets, gear boxes, etc.

The values given for eyebolts/eyenuts used with double-strand slings (cf. table line 2) apply only if the angle between each sling branch and the vertical does not exceed 45°. Larger angles and any lateral loading of eyebolts/eyenuts should be avoided.

... *Read more*

**Material:** AISI 316
**Marking:** According to standard
**Standard:** DIN 582


**CERTEX Danmark A/S**
info@certex.dk
+45 74 54 14 37

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

# Stainless Lifting Eye Nut DIN 582

## Blueprint




## Technical data

| Part code | WLL ton | Thread | d1 mm | d2 mm | d3 mm | d4 mm | h mm | k mm | Weight kg/100pc |
|---|---|---|---|---|---|---|---|---|---|
| 421100010130 | 0.14 | M8 | M8 | 20 | 36 | 20 | 36 | 8 | 5 |
| 421100020130 | 0.23 | M10 | M10 | 25 | 45 | 25 | 45 | 10 | 9 |
| 421100030130 | 0.34 | M12 | M12 | 30 | 54 | 30 | 53 | 12 | 16 |
| 421100070130 | 0.7 | M16 | M16 | 35 | 63 | 35 | 62 | 14 | 24 |
| 421100120130 | 1.2 | M20 | M20 | 40 | 72 | 40 | 71 | 16 | 36 |
| 421100180130 | 1.8 | M24 | M24 | 50 | 90 | 50 | 90 | 20 | 72 |

**CERTEX Danmark A/S**
info@certex.dk
+45 74 54 14 37

© November 2026 - All Rights Reserved