CERTEX | Lifting Solutions Group
Axel Johnson International

Pipe Suspension Grab

Product information



WiMAG

Indispensable pipe suspension grab for transport and pipe laying.
Reliable, no accidents, no damages.
Contact surface of clamp is steel/serrated.

- Gripping depth extended from 220 mm to 260 mm.
- Clamping range 90-200 mm (with rubber coating 50-150 mm).
- Simple and fast adjustment of the clamping range via threaded spindle.
- Gripping surfaces are grooved to prevent load slip.
- Rubber-lined clamps on request.
- Type 200D for prefabricated manholes according to DIN 4032 Part 1 with socket end for axial seal.
- Can also be used acc. to DIN 4032 Part 2.
- Other Wimag types according to DIN 4032 Part 2.
- Can be delivered with longer chains.

... *Read more*

Material: Clamp made of hollow sections, therefore torsion resistant and very light. Highstrength chains DIN 5687-5.

CERTEX Danmark A/S
info@certex.dk
+45 74 54 14 37

© November 2026 - All Rights Reserved

CERTEX | Lifting Solutions Group
Axel Johnson International

Pipe Suspension Grab

Technical data

Part code	Code	WLL ton	Jaw width mm	Number of clamps	Manhole inside dia. m	Chain length m	Weight kg
655600150000020	RSV 1,5	1.5	40-120	3	0,4-2,0	1,5	31
655600300000020	RSV 3	3	50-180	3	0,4-2,0	1,6	55

CERTEX Danmark A/S
info@certex.dk
+45 74 54 14 37

© November 2026 - All Rights Reserved