

## GKS Transport Trolley L12/F12

### Product information



The GKS worldwide approved transport trolleys solving your in-house heavy load standards - safe and perfect! Series F and L – the perfect 3-point moving solution for safe and simple transport. F trolleys – the rear axle of the load moving system with adjustable connecting bar to fit under heavy loads of almost any width. L trolleys – the front steering support with swivel top and tow eye to guide your loads safely. Wheels - special GKS wheels, that do not mark floors. Low rolling resistance and highest stability for numerous uses.

#### L12/F12 set:

- Standard transport set for heavy loads up to 24 tons.
- Can be combined with Tandem trolleys TL6/TL12 or rotating trolleys RL2 / RL4 / RL6

**Contact us for more possibilities! Sets available up to 120 t.**

| Part code | Type             | Loading height<br>mm | Number of wheels | Swivel plate dia.<br>mm | Wheels diameter<br>mm | Swivel pad steerable at | Width<br>mm | Contact surface<br>mm | Dimensions<br>mm   | Weight<br>kg | Delivery time |
|-----------|------------------|----------------------|------------------|-------------------------|-----------------------|-------------------------|-------------|-----------------------|--------------------|--------------|---------------|
| 900510312 | Rear, stationary | 110                  | 16               | -                       | 85x85                 | -                       | 1014-1430   | 200x407               | -                  | 52           | 10            |
| 900510313 | Front, steerable | 110                  | 16               | 170                     | 85x85                 | ± 90°                   | -           | -                     | (L) 1030 x (W) 620 | 80           | 10            |