

Mini Fall Arrest Block with Webbing - POWERTEX MBW25

Product information



Crafted with precision and built to last, our fall arrest mini block is designed to provide maximum protection and security in the most demanding environments. It's fitted with a top-quality black Dyneema® webbing, providing excellent protection in case you fall over an edge. The black-painted aluminum housing and integrated shock absorber guarantee durability and reliability.

Equipped with a fall indicator sewn into the webbing, our mini block offers advanced safety features that meets the EN 360 standard.

The block is versatile and can be attached to an anchor point or turned and attached to your safety harness. It is type-tested for vertical fall and against falling over an edge. The length of the scaffold hook and webbing remaining outside the house when retracted is just 0.6m, providing maximum flexibility and ease of use.

On top of the block, you'll find a swivel eye attachment point, and the block comes with a twist lock carabiner mounted to this swivel eye. A large double-action aluminum scaffold hook with eye is sewn to the end of the webbing on the bottom end. Finally, the block is RFID-equipped, completing the package.

Housing: Black painted aluminum

Shock absorber: Integrated into the housing

Carabiner: Twist lock carabiner, silver color, connected to swivel eye

Webbing: Black Dyneema® webbing

Fall indicator: Sewn into the webbing

Bottom Hook: Double action scaffolding hook, silver color

... [Read more](#)

Features: Integrated shock absorber, fall Indicator, RFID

Material: Aluminum, Dyneema, Steel

Marking: According to standard, CE-marked

Temperature range: -40°C up to +50°C

Finish: Black paint

Standard: EN 360

Mini Fall Arrest Block with Webbing - POWERTEX MBW25

Technical data

Part code	Length m	Max. rated load kg	Hook opening mm	Weight kg
822100250750	2.5	136	61	1.5