Lifting Solutions Group
Axel Johnson International

Anti-slip Mat Kargotec® Special Plus

Product information



Further improved, versatile anti-slip mat.
Kargotec® Spezial Plus is an anti-slip mat for securing the load, which is distinguished by good kinetic friction values. They are also used successfully as intermediate layer pads in the packaging industry.
Very high permissible surface pressure.

Thicknesses: 8 mm.
Max. permissible surface load (at max. 30% compression): approx. 180 t/m^2 at 3 mm thickness, approx. 290 t/m^2 at 8 mm thickness.
Kinetic friction coefficient μ: 0.81 at 3, 4, 5, 6, 8, 10 mm thickness.
Elongation at break: At least 60% (DIN EN ISO 1798).

... *Read more*

Material: Recycled rubber crumbs (particle size 1 – 3 mm), bonded with polyurethane.
Temperature range: -30°C up to +100°C
Finish: Black with coloured speckles

CERTEX Danmark A/S
info@certex.dk
+45 74 54 14 37

© November 2026 - All Rights Reserved

Anti-slip Mat Kargotec® Special Plus

Technical data

Part code	Dimensions mm	I'd like to have more information
709806609900	8X1250X8000	Kargotec Spezial

CERTEX Danmark A/S
info@certex.dk
+45 74 54 14 37

© November 2026 - All Rights Reserved