

## Anti-slip Mat Kargotec® Secure



### Product information

Anti-slip mat for extremely heavy loads.

Kargotec® secure is the anti-slip mat for heavy loads. The combination of an exceptionally high surface load capacity (max. 500 t/m<sup>2</sup> \*) and an excellent kinetic friction coefficient ( $\mu = 0.80$ ) makes this product the first choice when it comes to securing extremely heavy loads. Highest permissible surface pressure.

**Thickness:** 8 mm, 10 mm.

**Max. permissible surface load:** (at max. 30% compression) approx. 500 t/m<sup>2</sup> at 8, 10 mm thickness.

**Kinetic friction coefficient  $\mu$**  0.80 at 8 and 10 mm thickness.

**Elongation at break:** At least 80% (DIN EN ISO 1798).

**Features:** Registered colour coding system (black with blue and white speckles)

**Material:** Recycled rubber crumbs, bonded with polyurethane

**Temperature range:** -30°C up to +100°C

**Finish:** Grain texturing

Part code	Dimensions mm	I'd like to have more information	Delivery time
709806476700	8X1250X8000	Kargotec Secure	10
709806497600	8X1250X10000	Kargotec Secure	10
709806454900	10X1250X6000	Kargotec Secure	10
709806627100	8X1500X8000	Kargotec Secure	10