CERTEX | Lifting Solutions Group
Axel Johnson International

Fall Arrest Block IKAR HWS with Galvanized Wire

Product information



Robust, low-maintenance fall arrest device with galvanized wire and swivel. The swivel prevents the wire from twisting. Internal energy-absorber and hook with fall indicator.
Low weight and maintenance thanks to extra light aluminium housing.

Approved for vertical and horizontal use.

Edge tested: Tested at sharp edges, R ≥ 0,5 mm (CNB/P/11.060 2008 sharp edge Type A)

Carabiner: IKAR IKV21 (Lk = 186mm) small swivel snap hook (opening Ø 26 mm) Can be delivered with other carabiners or scaffolding hooks up on request.

The blocks can be delivered with the following approvals: ANSI/ASSE Z 359.14-2014/LE up on request.

... *Read more*


Material: Body: Aluminium
Marking: According to standard, CE-mark
Temperature range: -40ºC up to +50ºC.
Finish: Blue painted
Standard: EN 360

CERTEX Danmark A/S
info@certex.dk
+45 74 54 14 37

© November 2026 - All Rights Reserved

Fall Arrest Block IKAR HWS with Galvanized Wire

Blueprint



Technical data

Part code	Code	Max. number of persons	Length m	Max load kg	L mm	B mm	T mm	Weight kg
822100600620	41-HWS 6	1	6	136	400	145	80	3
822101200620	41-HWS 12	1	12	136	490	190	95	5.4
822101800620	41-HWS 18	1	18	136	540	220	97	6.9
822102400620	41-HWS 24	1	24	136	575	250	97	8.4

CERTEX Danmark A/S
info@certex.dk
+45 74 54 14 37
© November 2026 - All Rights Reserved