Lifting Solutions Group
Axel Johnson International

# Starcon Cast-in Lifting Loop

**Product information**



Starcon Cast-in Lifting Loop is a transport anchor that is embedded in concrete elements during the prefabrication phase and provides a safe lifting point for hoists. They are easily attached to a hook and are manufactured as an endless wire strap with alu-lock assembly. These wire rope straps are available in various sizes to suit different lifting capacities and applications.

**Areas of application:** Lift and secure precast concrete elements safely during transport and installation.
**Advantages:** Safe lifting and transport.
Easy to handle and install.
**Load group:** 0.8t – 25t
**Technical information:** CE marking according to MD 2006/42 EF
Starcon product is designed according to EN13155-2009 and follows the guidelines of VDI/BV-BS 6205 and DS/CEN/TR 15728.
**EPD:** Our Environmental Product Declarations (EPDs) are available in the LCA NO calculator/software. These EPDs have been prepared in strict accordance with ISO 14025 and EN 15804 standards.

Download the EPDs from the LCA database:
Untreated Products: Starcon Lifting and Handling Systems for Concrete elements - Untreated - EPD Norge
Surface treated Products: Starcon Lifting and Handling Systems for Concrete elements - Surface Treated. - EPD Norge

... *Read more*

**Marking:** CE-marked, load group + S(Starcon)
**Finish:** Electro-galvanized - Corrosion class C3 - ISO 12944-2.

**Note:** The delivery time for the individual products is estimated and if the desired quantity is not in stock, please contact CERTEX Danmark A/S – Starcon to get information about the applicable delivery time.


**CERTEX Danmark A/S**
info@certex.dk
+45 74 54 14 37

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

# Starcon Cast-in Lifting Loop

## Blueprint




## Technical data

| Part code | Load grp. t | Length mm | Wire Ø mm | D mm | L mm | B mm | Weight kg | Packing Qty. |
|---|---|---|---|---|---|---|---|---|
| 65041000800 | 0.8 t | 200 | 6 | 6 | 200 | 85 | 0.09 | 50 |
| 65041001200 | 1.2 t | 225 | 7 | 7 | 225 | 90 | 0.12 | 50 |
| 65041001600 | 1.6 t | 235 | 8 | 8 | 235 | 100 | 0.15 | 50 |
| 65041002000 | 2 t | 265 | 9 | 9 | 265 | 125 | 0.25 | 50 |
| 65041002500 | 2.5 t | 285 | 10 | 10 | 285 | 145 | 0.34 | 40 |
| 65041004000 | 4 t | 345 | 12 | 12 | 345 | 170 | 0.5 | 25 |
| 65041005200 | 5.2 t | 390 | 14 | 14 | 390 | 195 | 0.99 | 15 |
| 65041006300 | 6.3 t | 415 | 16 | 16 | 415 | 210 | 1.05 | 1 |
| 65041008000 | 8 t | 460 | 18 | 18 | 460 | 225 | 1.49 | 1 |
| 65041010000 | 10 t | 510 | 20 | 20 | 510 | 225 | 2.06 | 1 |
| 65041012500 | 12.5 t | 570 | 22 | 22 | 570 | 295 | 3.31 | 1 |
| 65041016000 | 16 t | 640 | 26 | 26 | 640 | 320 | 4.5 | 1 |
| 65041020000 | 20 t | 715 | 28 | 28 | 715 | 355 | 5.5 | 1 |
| 65041025000 | 25 t | 800 | 30 | 30 | 800 | 400 | 8.2 | 1 |

**CERTEX Danmark A/S**
info@certex.dk
+45 74 54 14 37

© November 2026 - All Rights Reserved