
CERTEX | Lifting Solutions Group
Axel Johnson International

Transport Anchor Solid Material Starcon

Product information



The Starcon transport anchor is made of solid material and has a cross hole through which a reinforcing rod is passed to anchor the anchor. These anchors can be used in various concrete elements due to the flexible arrangement options with the reinforcing bar. The anchor is ideal for lifting thin precast elements or elements with low concrete strength.

The transport anchor solid material is available with a metric thread, which makes it easy to attach wire rope straps and threaded lifting gear products by screwing them onto the transport anchor. This ensures an efficient and safe lifting operation.

Areas of application: Thin or low concrete strength elements or beam elements.
Advantages: Perfect for thin precast walls or low-performance concrete.
Low unladen weight
Load group: 0.4t – 4t
Technical information: CE marking according to MD 2006/42 EF
Starcon product is designed according to EN13155-2009 and follows the guidelines of VDI/BV-BS 6205 and DS/CEN/TR 15728.
EPD: Our Environmental Product Declarations (EPDs) are available in the LCA NO calculator/software. These EPDs have been prepared in strict accordance with ISO 14025 and EN 15804 standards.

Download the EPDs from the LCA database:
Untreated Products: Starcon Lifting and Handling Systems for Concrete elements - Untreated - EPD Norge
Surface treated Products: Starcon Lifting and Handling Systems for Concrete elements - Surface Treated. - EPD Norge

... *Read more*

Marking: CE-mark, Thread size, batch code, load group + S(Starcon)
Finish: Electro-galvanized - Corrosion class C3 - ISO 12944-2. Stainless (AISI 316) - Corrosion class C5 - ISO 12944-2.

Note: The delivery time for the individual products is estimated and if the desired quantity is not in stock, please contact CERTEX Danmark A/S – Starcon to get information about the applicable delivery time.


CERTEX Danmark A/S
info@certex.dk
+45 74 54 14 37

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Transport Anchor Solid Material Starcon

Blueprint



Technical data

Part code	Thread mm	Length mm	Finish	L mm	D mm	d mm	e mm	M mm	f mm	Weight kg	Packing Qty.
650560NK3310VA	M10	42	Stainless	42	16	9	21	M10	5	0.045	250
650560NK3312VA	M12	49	Stainless	49	18	11	20	M12	5	0.065	250
650560NK3316VA	M16	56	Stainless	56	22	14	23	M16	7	0.13	150
650561K3316ZN	M16	56	White zinc plated	56	22	14	23	M16	7	0.134	150
650560NK3320VA	M20	68	Stainless	68	28	16	28	M20	9	0.23	75
650561K3320ZN	M20	68	White zinc plated	68	28	16	28	M20	9	0.25	75
650560NK3324VA	M24	80	Stainless	80	32	21,5	35	M24	13	0.32	50
650561K3324ZN	M24	80	White zinc plated	80	32	21,5	35	M24	13	0.345	50
650560NK3330VA	M30	103	Stainless	103	40	22	45	M30	15	0.65	25
650561K3330ZN	M30	103	White zinc plated	103	40	22	45	M30	15	0.663	25

CERTEX Danmark A/S
info@certex.dk
+45 74 54 14 37

© November 2026 - All Rights Reserved