



STA-ST Sandwich Anchor Starcon

Product information

The Starcon STA-ST is perfect for prefabricated sandwich elements, as the suspension point is located near the center of gravity, ensuring upright transport and assembly.

The anchor head has a hole for mounting the ring coupling and additional holes for rebar reinforcement, allowing for a solid anchoring in the concrete element and application for various lifting applications. The STA-ST anchor is the optimal solution for transporting and mounting sandwich elements.

Areas of application: Sandwich elements

Advantages: Ensures that the sandwich element has minimal tilt during transport and assembly. Quick connection/disconnection with the former- and Starcon ring coupling, perfect for efficient transport and setup.

Load group: 2.5t – 17t

Technical information: CE marking according to MD 2006/42 EF

Starcon product is designed according to EN13155-2009 and follows the guidelines of VDI/BV-BS 6205 and DS/CEN/TR 15728.

EPD: Our Environmental Product Declarations (EPDs) are available in the LCA NO calculator/software. These EPDs have been prepared in strict accordance with ISO 14025 and EN 15804 standards.

Download the EPDs from the LCA database:

Untreated Products: [Starcon Lifting and Handling Systems for Concrete elements - Untreated - EPD Norge](#)

Surface treated Products: [Starcon Lifting and Handling Systems for Concrete elements - Surface Treated. - EPD Norge](#)

Marking: CE-marked, batch code, load group + S(Starcon)

Finish: Untreated - Corrosion class C1 - ISO 12944-2. Hot-dip galvanized - Corrosion class C3 - ISO 12944-2

Note: The delivery time for the individual products is estimated and if the desired quantity is not in stock, please contact [CERTEX Danmark A/S – Starcon](#) for information on the applicable delivery time.

Part code	Load grp. t	Length mm	Finish	a mm	b1 mm	b2 mm	c mm	L mm	r mm	Hole mm	Weight kg	Delivery time
65012502502501	2.5	250	Untreated	40	14	18	10	250	7	14x20	0.7	2
65012502502502	2.5	250	HDG	40	14	18	10	250	7	14x20	0.7	10
65012505003001	5	300	Untreated	60	18	26	15	300	9	18x22	1.89	2
65012505003002	5	300	HDG	60	18	35	15	300	9	18x22	1.89	2
65012507503501	7.5	350	Untreated	80	26	35	15	350	13	26x30	2.8	2
65012507503502	7.5	350	HDG	80	26	35	15	350	13	26x30	2.8	2
65012510003501	10	350	Untreated	80	30	35	20	350	14	26x30	3.59	2
65012510003502	10	350	HDG	80	30	35	20	350	14	26x30	3.59	2
65012517004001	17	400	Untreated	100	30	35	25	400	17.5	35x46	6.45	2
65012517004002	17	400	HDG	100	30	35	25	400	17.5	35x46	6.45	2

Blueprint

