# Lifting Socket with short-wavy Tail Bar

**Product information**



Lifting Socket with short-wavy Tail Bar is attached to a reinforcing bar and is particularly suitable for embedding in wall-type elements perpendicular to the level of the wall, where a straight bar may not be suitable. Due to the relatively short length of the anchor pole, these transport anchors provide a strong and reliable connection point for lifting, transporting and handling.

The bent short reinforcement bar ensures a solid anchoring in the concrete element. Additional reinforcement can be installed when needed. The head of the transport anchor is cylindrical with internal thread and is available in both metric and round threads, making it easy to attach wire rope straps and threaded lifting equipment by screwing these onto the transport anchor. This ensures an efficient and safe lifting operation.

**Areas of application:** Walls, floorboards or stairs.
**Advantages:** Quick connection and detachment for wire rope.
**Load group:** 0.5t – 6.3t
**Technical information:** CE marking according to MD 2006/42 EF

The product is designed according to EN13155-2009 and follows the guidelines of VDI/BV-BS 6205 and DS/CEN/TR 15728.

... *Read more*

**Material:** The head is made of the S355. Rebar in B500B according to DIN488
**Marking:** CE-mark, Threaded size
**Finish:** Electro-galvanized - Corrosion class C3 - ISO 12944-2.

**Note:** The delivery time for the individual products is estimated and if the desired quantity is not in stock, please contact CERTEX Danmark A/S – Starcon to get information about the applicable delivery time.

**CERTEX Danmark A/S**
info@certex.dk
+45 74 54 14 37

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

# Lifting Socket with short-wavy Tail Bar

## Blueprint




## Technical data

| Part code | Thread mm | Length mm | d mm | L mm | g mm | ds mm mm | Weight kg/100pc | Packing Qty. |
|---|---|---|---|---|---|---|---|---|
| 650545K3112KM | M12 | 150 | M12 | 150 | 25 | 8 | 0.085 | 150 |
| 650545K3116KM | M16 | 230 | M16 | 230 | 27 | 12 | 0.268 | 40 |
| 650545K3120KM | M20 | 260 | M20 | 260 | 34 | 14 | 0.45 | 20 |
| 650545K3124KM | M24 | 300 | M24 | 300 | 43 | 16 | 0.668 | 1 |
| 650545K3130KM | M30 | 420 | M30 | 420 | 56 | 20 | 1.426 | 1 |
| 650545K3136KM | M36 | 460 | M36 | 460 | 69 | 25 | 2.533 | 1 |
| 650545K3152KM | M52 | 550 | M52 | 550 | 100 | 32 | 5.16 | 1 |

**CERTEX Danmark A/S**
info@certex.dk
+45 74 54 14 37

© November 2026 - All Rights Reserved