

Wall Jib Crane PMT

Product information

General

Appropriate for an indoor or outdoor use, the beam of the PMT is built on an I beam profile. Its light weight gives it great flexibility for rotations of 180°. The structure of this jib crane is suitable for the optional installation of a hoist motor direction. The PMT are delivered with standard mounting brackets and our mounting kits KITFIX (optional) ensure safe anchorages for specific supports.

A full range of accessories is available.

Options

- Hoist power supply cable + lockable main switch
- Standpipe
- Rotation slowing device (adaptable without welding or mechanical intervention)
- Hot dip galvanizing (contact us)
- Rotation stops to weld onto the assembly
- Single- or multi-position rotation lock
- Outdoor use
- Electric or manual hoist

Technical data

| Outreach (m) / Capacity (kg) | 2,5 | 3 | 3,5 | 4 | 4,5 | 5 | 6 | 6,5 | 7 | 7,! |
|------------------------------|-----|---|-----|---|-----|---|---|-----|---|-----|
| 125 | X | x | Х | x | х | Х | х | х | Х | X |
| 250 | Х | x | X | X | X | Х | Х | Х | Х | X |
| 500 | Х | x | X | X | X | Х | Х | Х | Х | X |
| 1000 | Х | X | X | X | X | Х | Х | X | Х | Х |
| 1600 | Х | х | х | X | Х | Х | Х | | | |
| 2000 | x | X | Х | X | X | Х | Х | | | |