

Lifting Socket flat End and Cross-hole



Product information

Lifting socket with flat end and cross-hole. It is used with a reinforced bar passed through the hole to anchor the socket. Owing to the flexible anchorage options, these sockets can be used in diverse components - walls, slabs, pipes, etc.
The thread is cut oversize.

This product complies with the requirements of European Machinery Directive 2006/42/EC.

Material: Lifting sockets made from steel tube for precision applications to DIN EN 10305 (grade E 355+N)

Marking: According to standard, CE-marked

Finish: Galvanized

Standard: CEN/TR 15728 - VDI/BV-BS 6205

Safety factor: 3:1

Part Code	dxL mm	e mm	g mm	Weight kg/100pc	Delivery time
6501K3010ZN	M 10x50	10.3	22	3.1	100
6501K3012ZN	M 12x60	10.3	25	4.1	2
6501K3016ZN	M 16x79	13.3	27	11.1	2
6501K3020ZN	M 20x99	15.3	37	22	2
6501K3024ZN	M 24x112	17.3	43	30	2
6501K3030ZN	M 30x156	19.5	56	76.6	2

Technical data

U-bar anchorage B500B			
d	d	D	G
mm	mm	mm	mm
M 10	8	60	250
M 12	8	60	300
M 16	10	70	350
M 20	12	80	400
M 24	14	100	450
M 30	16	130	600

Blueprint

