





Elevator



Certlift 8F - Elevator

Product information



Typical applications: For elevators.

Design: Ordinary right hand lay.

Features: Fibre core as lubrication reservoir, durable, smooth running and robust design.

Rope construction: 8x19 Seal + FC.

Marking: According to standard

Finish: Ungalvanized.

Standard: EN 12385-5

Fill factor: 0.44

Part code	Rope diameter mm	Tensile strength N/mm²	Steel area mm²	Min. breaking force kN	Finish	Rope lay	Weight kg/100m	Delivery time
106100804130111	8	1,370/1,770	22.3	28.1	Bright	sZ	21.8	10
106100904130111	9	1,370/1,770	28.3	35.6	Bright	sZ	27.5	10
106101004130111	10	1,370/1,770	34.9	44	Bright	sZ	34	10
106101104130111	11	1,370/1,770	42.2	53.2	Bright	sZ	41.1	10
106101204130111	12	1,370/1,770	50.3	66.3	Bright	sZ	49	10
106101304130111	13	1,370/1,770	59	74.3	Bright	sZ	57.5	10
106101404130111	14	1,370/1,770	68.4	86.2	Bright	sZ	66.6	10
106101504130111	15	1,370/1,770	78.5	98.9	Bright	sZ	76.5	10
106101604130111	16	1,370/1,770	89.3	113	Bright	sZ	87	10