

Vacuum Lifter AERO-VARIOWIN

Product information

Thanks to depth-adjustable suction plates, this vacuum lifter solves the problem of handling workpieces with offset webs (e.g., glass in prefabricated house construction). 3-hole suspension eye compensates the centre of gravity, and the workpiece can be rotated vertically by +/- 90° and fixed every 15° using a Bowden cable. Possibility of handling smaller formats thanks to the additional shorter crane suspension. With height-adjustable suspension points.

Thanks to the special AERO-LIFT glass suction plates, which have a low intrinsic volume and a unique structure, the vertical position experiences excellent suction properties and an increased friction coefficient. It can handle workpieces with a web offset up to max. 13 cm.

Product variants

The AERO-VARIOWIN vacuum lifter is available in more versions with:

- Load capacities from 250 kg up to 500 kg
- · Different suction plate diameters etc.

| Part code | WLL ton | Model | D mm | L mm | B EH mm | L EH mm | EH mm | Weight kg | Delivery time |
|-------------|------------|--------------------|---------|---------|---------|---------|-------|--------------|---------------|
| 56051031936 | 0.25 | AE-VARIOWIN 250/4G | 270 | 1,625 | 25 | 36 | 3,280 | 135 | 10 |
| 56051031938 | 0.5 | AE-VARIOWIN 500/4G | 360 | 360 | 25 | 36 | 4,580 | 140 | 10 |

Blueprint

