Lifting Solutions Group
Axel Johnson International

J-hook 60T for lifting of Tower Sections

Product information



This lifting hook for tower section lifting or other cylindrical items with an inside diameter with a flange, is designed as a C-hook following EN 13155, terms and definitions. It is designed to support the windmill tower section, when it is lifted and transported in a horizontal attitude..

The lifting hook has a special lifting eye designed for a looped lifting sling, allowing connection to a double crane hook. We recommend an Extreema round sling, WLL 30 t, 1,5/3,0-meter EXHCO30/1,5A (ordered separately).

The cradle is protected with plastic plates and hard-formed rubber on the load plate to resist metal-to-metal contact. The lifting hook has an additional plate under it, which allows it to be stored standing up.

... *Read more*

Marking: According to standard, CE-mark
Temperature range: -10ºC up to + 50ºC
Standard: EN 13155
Note: User manual available on request
Warning: Wind speed: Maximum up to 10m/sec

CERTEX Danmark A/S
info@certex.dk
+45 74 54 14 37

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

J-hook 60T for lifting of Tower Sections

Blueprint

Technical data

Part code	WLL ton	Dimensions mm	Weight kg
420506001680	60	600 (L) x220 (W) x 1390 (H)	360

CERTEX Danmark A/S
info@certex.dk
+45 74 54 14 37

© November 2026 - All Rights Reserved