

Swivel Bearing Hook POWERTEX SHS-B

Product information



The POWERTEX Sling Hook SHS-B with a ball-bearing swivel is part of the Powertex G10 Lifting Sling Chain Components range. Using the sling hook is very easy as it can be quickly attached to lifting points. Its sturdy latch ensures security. Moreover, the eye of the hook is designed with a ball-bearing swivel, allowing for both loaded and unloaded rotation.

Available for 6 mm up to 16 mm chain and from WLL 1.4t up to WLL 10t.

Powerdex G10 Range benefits:

- 25% higher capacity compared to traditional Grade 8 components
- All POWERTEX G10 components are painted in luminous red
- Multi-functional master links and components are included in the range to allow quick and cost-effective assembly of chain slings
- The components meet EN 1677 part 1/2/3/4 +25% WLL
- Each forged component is crack detection tested, and samples are proof load tested.
- Each component is type tested in the factory and fatigue rated to 20,000 cycles at 1.5 times the WLL
- Full traceability through a batch number
- Replacement spare parts available
- All components are chromium 6 free
- POWERTEX 2.2 certificate enclosed with each box of components
- The components may also be used with Grade 8 chain to EN 818-2. In such a case, the chain sling needs to be rated as Grade 8 in accordance with [EN 818-2](#) ... [Read more](#)

Marking: According to standard, POWERTEX + Model (SHS-6-10B) + traceability code.

Temperature range: -40°C up to +200°C without reduction in WLL

Finish: Powder painted in luminous red


Standard: EN 1677-2 (+25% WLL), AS 3776

Safety factor: 4:1

Grade: 10

Swivel Bearing Hook POWERTEX SHS-B

Blueprint



Technical data

| Part code | Code | Chain diameter mm | WLL ton | EWL mm | A mm | B mm | C mm | E mm | H, mm | L mm | L1mm mm | Mmm mm | Nmm mm | Weight kg |
|--------------|------------|-------------------|---------|--------|------|------|------|------|-------|------|---------|--------|--------|-----------|
| 402300141460 | SHS-6-10B | 6 | 1.4 | 141 | 37 | 32.5 | 11.5 | 24 | 19 | 173 | 141 | 71 | 16 | 0.65 |
| 402300251460 | SHS-8-10B | 8 | 2.5 | 171 | 41.6 | 41 | 13 | 28.5 | 26 | 213 | 171 | 88 | 20 | 0.95 |
| 402300401460 | SHS-10-10B | 10 | 4 | 216 | 51 | 48 | 15.5 | 34 | 29.5 | 263 | 216 | 105 | 25 | 1.7 |
| 402300671460 | SHS-13-10B | 13 | 6.7 | 253 | 59 | 55 | 17 | 40 | 38 | 310 | 253 | 135 | 32 | 3.1 |
| 402301001460 | SHS-16-10B | 16 | 10 | 293 | 68 | 61 | 21.5 | 45 | 45 | 364 | 293 | 161 | 37.5 | 5.4 |