

Polypropylene Fibre Rope 3-Strand.

Product information



Fibre rope of polypropylene for all different kinds of applications like: tarpaulin- and towing-ropes, lifting slings, ropes for the fishing industry, cargo nets, rope ladders, and more. The structure of the fibre rope makes it non-sliding in knots and splices.

Design: Spliced fibre.

Specific gravity: 0,91 (floats).

Melting point: Approx. 165°C.

Elongation at MBL: Approx. 30%.

Strength wet/dry: 100%

Shock Absorption: Very Good

Water Absorption: None

Abrasion Resistance: Good

... [Read more](#)

Material: Polypropylene, resistant to rot, most acids and alkalies. The fibre is UV-stabilized against sunlight.

Marking: According to standard

Finish: Blue.

Standard: EN ISO 1346

Polypropylene Fibre Rope 3-Strand.

Technical data

| Part code | Diameter mm | MBL | Length m | Circ. inches | Weight kg/220m |
|-----------------|----------------|------|-------------|-----------------|-------------------|
| 300300402200010 | 4 | 0.28 | 220 | 3 | 1.54 |
| 300300502200010 | 5 | 0.45 | 220 | 3 1/4 | 2.42 |
| 300300602200010 | 6 | 0.55 | 220 | 3 1/2 | 3.52 |
| 300300802200010 | 8 | 0.96 | 220 | 3 3/4 | 6.38 |
| 300301002200010 | 10 | 1.43 | 220 | 4 | 9.9 |
| 300301202200010 | 12 | 2.03 | 220 | 4 1/2 | 14.3 |
| 300301402200010 | 14 | 2.79 | 220 | 5 | 19.58 |
| 300301602200010 | 16 | 3.5 | 220 | 5 1/2 | 25.52 |
| 300301802200010 | 18 | 4.45 | 220 | 6 | 32.12 |
| 300302002200010 | 20 | 5.37 | 220 | 3 | 39.82 |
| 300302202200010 | 22 | 6.5 | 220 | 3 1/4 | 48.18 |
| 300302402200010 | 24 | 7.6 | 220 | 3 | 57.2 |
| 300302602200010 | 26 | 8.45 | 220 | 3 1/4 | 67.32 |
| 300302802200010 | 28 | 10.1 | 220 | 3 1/2 | 77.88 |
| 300303202200010 | 32 | 12.8 | 220 | 4 | 101.86 |
| 300303602200010 | 36 | 16.1 | 220 | 4 1/2 | 128.92 |