



## Spur Gear Hand Winch TL300-600 Painted

### Product information

This convenient spur gear winch excels by its speed. It is equipped with a load-pressure brake with a double ratchet system and a semi-closed housing. In short, a fine, easy winch!

- robust and safe lifting and pulling winch
- load pressure brake with double ratchet system for safe stable hold of the load in any position
- cable outlet upwards
- adjustable crank
- suitable for wall mounting
- 1 layer of paint

#### Options:

- zinc-plated finish 6 - 8 micron (EV)
- 2 layers of paint (2L)
- ATEX certified zone 2 and 22 (EX)  
CE II 3G Ex IIC T4 Gc, -20°C<T amb <+70°C  
CE II 3D Ex IIIC T135°C Dc, -20°C<T amb <+70°C

**Material:** Steel

**Marking:** According to standard, CE-marked

**Temperature range:** -20°C up to +70°C

**Finish:** Painted, grey

**Standard:** EN 13157

**Note:** The cable must be ordered separately, ask for more information about our sales

**Safety factor:** 4:1

| Part code       | Code  | WLL ton | Rope Ø mm | Rope capacity m | Capacity 1st layer kg | Capacity top layer kg | Weight kg | Delivery time |
|-----------------|-------|---------|-----------|-----------------|-----------------------|-----------------------|-----------|---------------|
| 501300030000560 | TL300 | 0.3     | 4         | 35.4            | 300                   | 172                   | 10        | 10            |
| 501300060000560 | TL600 | 0.6     | 6         | 12.3            | 600                   | 336                   | 11        | 10            |

## Blueprint

