

Chain Block POWERTEX PCB-S2

Product information



The Powertex PCB-S2 Hoist is a high-quality chain block designed to provide durability, safety, and ease of operation. With its ergonomic hand chain and advanced features, this chain hoist ensures smooth and efficient lifting for various industrial applications.

Product benefits:

- **Enhanced safety:** each hoist undergoes dynamic proof load testing at 1.5 times the Working Load Limit (WLL) before leaving the factory, ensuring maximum safety and reliability. The hoist is equipped with a well-covered automatic load reaction brake and features double safety with two brake pawls and four brake springs, exceeding EN 13157 requirements. The load chain is calibrated, proof load tested and meets the requirements of EN 818-7.
- **Smooth and efficient Operation:** the compact and lightweight construction, combined with a sprocket wheel equipped with needle bearings and a drive shaft supported by needle and slide bearings, ensures smooth and efficient operation. The fine-calibrated load chain offers quiet and seamless performance.
- **Quality load chain:** the load chain complies with the EN818-7 T(8) standard and features a Chrome 6-free electro-galvanized surface finish to protect it from corrosion.
- **Easy positioning and safe hooks:** swivel hooks at both ends make in-line positioning easy. The hooks are designed to open at overload instead of breaking, enhancing safety. Heavy-duty steel safety latches and deformation check dots forged into the side of the hooks allow for easy overload detection.
- **Convenient maintenance and documentation:** each hoist is RFID-equipped for ... [Read more](#)

Material: Durable all steel construction

Marking: According to standard, CE-marked, UKCA-marked, POWERTEX, Model, WLL, Chain, Serial number, User manual/QR code

Temperature range: -10°C up to +50°C

Finish: Red powder coated body and plated frame components


Standard: EN 13157, EN 818-7

Safety factor: 4:1

Also available with COROLIM® surface-treated load chain. The unique COROLIM® surface treatment of the load chain provides excellent corrosion protection, equivalent to ISO944-9 C5 High / ISO9223 C3 standards, ensuring long-lasting durability even in harsh environments.

Chain Block POWERTEX PCB-S2

Blueprint



Technical data

| Part code | WLL ton | Lifting height m | Number of falls | Model | Load chain mm | Hand chain mm | Hand force max. kg | A mm | B mm | C mm | D mm | H min mm | Weight kg |
|-----------------|---------|------------------|-----------------|--------------------|---------------|---------------|--------------------|------|------|------|------|----------|-----------|
| 500100030300670 | 0.25 | 3 | 1 | PCB-S2/250KG PHCA | 4,0 x 12,0 | 5,0 x 23,7 | 23.5 | 108 | 106 | 20 | 30 | 260 | 5.9 |
| 500100030600670 | 0.25 | 6 | 1 | PCB-S2/250KG PHCA | 4,0 x 12,0 | 5,0 x 23,7 | 23.5 | 108 | 106 | 20 | 30 | 260 | 6.4 |
| 500100050300670 | 0.5 | 3 | 1 | PCB-S2/500KG PHCA | 5,0 x 15,0 | 5,0 x 23,7 | 24.9 | 130 | 128 | 22 | 34 | 280 | 9.8 |
| 500100050600670 | 0.5 | 6 | 1 | PCB-S2/500KG PHCA | 5,0 x 15,0 | 5,0 x 23,7 | 24.9 | 130 | 128 | 22 | 34 | 280 | 14 |
| 500100100300670 | 1 | 3 | 1 | PCB-S2/1000KG PHCA | 6,3 x 19,0 | 5,0 x 23,7 | 28.4 | 150 | 145 | 26 | 39 | 330 | 11.7 |
| 500100100600670 | 1 | 6 | 1 | PCB-S2/1000KG PHCA | 6,3 x 19,0 | 5,0 x 23,7 | 28.4 | 150 | 145 | 26 | 39 | 330 | 16.95 |
| 500100200300670 | 2 | 3 | 1 | PCB-S2/2000KG PHCA | 8,0 x 24,0 | 5,0 x 23,7 | 34.3 | 185 | 175 | 35 | 49 | 385 | 18.9 |
| 500100200600670 | 2 | 6 | 1 | PCB-S2/2000KG PHCA | 8,0 x 24,0 | 5,0 x 23,7 | 34.3 | 185 | 175 | 35 | 49 | 385 | 19.5 |
| 500100300300670 | 3 | 3 | 2 | PCB-S2/3000KG PHCA | 7,1 x 21,0 | 5,0 x 23,7 | 34.3 | 220 | 158 | 37 | 50 | 510 | 28.9 |
| 500100300600670 | 3 | 6 | 2 | PCB-S2/3000KG PHCA | 7,1 x 21,0 | 5,0 x 23,7 | 34.3 | 220 | 158 | 37 | 50 | 510 | 28.9 |
| 500100500300670 | 5 | 3 | 2 | PCB-S2/5000KG PHCA | 9,0 x 27,0 | 5,0 x 23,7 | 37.2 | 255 | 183 | 43 | 60 | 615 | 37.1 |
| 500100500600670 | 5 | 6 | 2 | PCB-S2/5000KG PHCA | 9,0 x 27,0 | 5,0 x 23,7 | 37.2 | 255 | 183 | 43 | 60 | 615 | 45.05 |