Lifting Solutions Group
Axel Johnson International

Battery for evo5 to evo25 Elebia

Product information



No connectors or wires. No cover. Push to insert. Pull to remove. Simple.
Lock system to prevent the battery from falling in case of impact.
ON/OFF button.
Ergonomic rubber handle to pull and carry the battery.
You'll always know the level of the battery thanks to the 4 high brightness LEDs.
Save battery when the evo automatic hooks are not in use.

... *Read more*

CERTEX Danmark A/S
info@certex.dk
+45 74 54 14 37

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Battery for evo5 to evo25 Elebia

Technical data

Part code	Code	Weight kg
6097EVO1700	evo 1700	0.39

Technical Specifications:

Technology	____	Rechargeable Li-Ion
Maximum Voltage	____	24.8V DC
Nominal Voltage	____	22.2V DC
Nominal Capacity	____	2.6Ah DC
Protection Circuit	____	Charge, Discharge, Overvoltage
Maximum Discharge Current	____	6A
Heat Protection	____	Thermal 70 ºC/*158 ºF*
Charge Indicator	____	Display ON 4 LED (25%-50%-75%-100%)
Temperature (Charge)	____	0 ºC to 45 ºC/*32 ºF to 113 ºF*
Temperature (Discharge)	____	-20 ºC to 50 ºC/*-4 ºF to 122 ºF*
Temperature (Idle)	____	-20 ºC to 60 ºC/*-4 ºF to 140 ºF*

CERTEX Danmark A/S
info@certex.dk
+45 74 54 14 37
© November 2026 - All Rights Reserved