Battery evo2 Elebia

Product information



The battery status is indicated by a 14 segment Eink display.
It is fully charged when the 14 Eink segments are black, and as the battery discharges the segments turn white. The battery is completely discharged when all 14 Eink segments are white.
With the new Eink charge status display system and new electronics, autonomy and consumption are optimized.
Save battery when the lifting product is not in use.

... *Read more*

CERTEX Danmark A/S
info@certex.dk
+45 74 54 14 37

© November 2026 - All Rights Reserved

CERTEX | Lifting Solutions Group
Axel Johnson International

Battery evo2 Elebia

Technical data

Part code	Code	Weight kg
6097EVO21700	evo2 1700	0.15

Technical Specifications:

Technology	____	Rechargeable Li-Ion
Maximum Voltage	____	12.4V DC
Nominal Voltage	____	10.95V DC
Nominal Capacity	____	3.2Ah DC
Protection Circuit	____	Charge, Discharge, Overvoltage
Maximum Discharge Current	____	6.4A
Heat Protection	____	Thermal 70 ºC/*158 ºF*
Charge Indicator	____	Eink 14 Segment Display
Temperature (Charge)	____	0 ºC to 45 ºC/*32 ºF to 113 ºF*
Temperature (Discharge)	____	-20 ºC to 50 ºC/*-4 ºF to 122 ºF*
Temperature (Idle)	____	-20 ºC to 60 ºC/*-4 ºF to 140 ºF*
Weight	____	150 g/*5.29 oz.*

CERTEX Danmark A/S
info@certex.dk
+45 74 54 14 37

© November 2026 - All Rights Reserved