Lifting Solutions Group
Axel Johnson International

Fall Arrest Block IKAR Flexible HWB 2 X

Product information



Fall arrest block single with webbing and swivel suspension, which prevents the webbing from twisting. Integrated energy-absorber and retractable lanyard.

Seawater-resistant aluminum housing with retractable lanyard made of almost indestructible Dyneema® webbing.

Approved for vertical and horizontal use.

Edge tested: Tested at sharp edges, R ≥ 0,5 mm (CNB/P/11.060 2008 sharp edge Type A)
Carabiner: IKV 32 with opening width 66 mm in the bottom

... *Read more*

Material: Housing: aluminium, webbing: Dyneema®
Marking: According to standard, CE-mark
Temperature range: -40ºC up to 50ºC
Finish: Blue painted
Standard: EN 360


CERTEX Danmark A/S
info@certex.dk
+45 74 54 14 37

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Fall Arrest Block IKAR Flexible HWB 2 X

Blueprint



Technical data

Part code	Code	Max. number of persons	Length m	Max load kg	B mm	L mm	T mm	Weight kg
822100250670	HWB 2 X	1	2.5	136	94	273	69	1.1

CERTEX Danmark A/S
info@certex.dk
+45 74 54 14 37

© November 2026 - All Rights Reserved