



Ring Clutch with Extreema® XS Round Sling Starcon

Product information

The Starcon ring clutch with Extreema® XS round sling is a specially designed component with a bolt-shaped ring that grips the hole of the STA anchor. It enables quick and secure mounting of the ring coupling to the STA anchors using a locking bolt that mechanically locks to the anchor.

The Starcon ring clutch with Extreema® XS round sling can be easily connected to a sling or hook, making lifting both quick and safe. It is ideal for use with lifting equipment and cranes, ensuring efficient and reliable handling of concrete elements.

Areas of application: The ring clutch with Extreema® XS round sling is used for lifting the Starcon STA anchor.

Advantages: Ensures handling of concrete elements.

Enables safe lifting in all directions.

Quick and easy installation.

Lightweight and easy handling of the product.

Load group: 5T – 26T

Technical information: CE marking according to MD 2006/42 EF

Starcon product is designed according to EN13155-2009 and follows the guidelines of VDI/BV-BS 6205 and DS/CEN/TR 15728.

Marking: CE-marked, batch code, load group + S(Starcon)

Finish: Electro-galvanized - Corrosion class C3 - ISO 12944-2

Note: The delivery time for the individual products is estimated and if the desired quantity is not in stock, please contact [CERTEX Danmark A/S – Starcon](#) to get information about the applicable delivery time.

Part code	EWL m	Load grp. t	c mm	dmm mm	dsl mm mm	EWL mm mm	Weight kg	Packing Qty.	Delivery time
650291050001DR	0.5	5	107	37	14	500	1.58	1	10
650291025001DR	0.25	10	148	50	23	250	3.78	1	10
650296260001DR	1	26	200	72	45	1,000	14.94	1	10

Blueprint

