



## Ring Clutch with Extreema® XS Round Sling Starcon

## **Product information**

The Starcon ring clutch with Extreema<sup>®</sup> XS round sling is a specially designed component with a bolt-shaped ring that grips the hole of the STA anchor. It enables quick and secure mounting of the ring coupling to the STA anchors using a locking bolt that mechanically locks to the anchor.

The Starcon ring clutch with Extreema<sup>®</sup> XS round sling can be easily connected to a sling or hook, making lifting both quick and safe. It is ideal for use with lifting equipment and cranes, ensuring efficient and reliable handling of concrete elements.

Areas of application: The ring clutch with Extreemd® XS round sling is used for lifting the Starcon STA anchor. Advantages: Ensures handling of concrete elements. Enables safe lifting in all directions. Quick and easy installation. Lightweight and easy handling of the product. Load group: 5T – 26T Technical information: CE marking according to MD 2006/42 EF Starcon product is designed according to EN13155-2009 and follows the guidelines of VDI/BV-BS 6205 and DS/CEN/TR 15728.

Marking: CE-marked, batch code, load group + S(Starcon) Finish: Electro-galvanized - Corrosion class C3 - ISO 12944-2

Note: The delivery time for the individual products is estimated and if the desired quantity is not in stock, please contac<u>CERTEX Danmark</u> <u>A/S – Starcon</u> to get information about the applicable delivery time.

Part code	EWL m	Load grp. t	c mm	d mm	dsl mm	EWL mm	Weight kg	Delivery time
650291050001DR	0.5	5	107	37	14	500	1.58	10
650291025001DR	0.25	10	148	50	23	250	3.78	10
650296260001DR	1	26	203	72	45	1,000	14.94	10

## Blueprint

