Lifting Solutions Group
Axel Johnson International

Fall Arrest Block IKAR Flexible HWB 2,0 DWX

Product information



Fall arrest block double with webbing and swivel suspension, which prevents the webbing from twisting. Integrated energy-absorber and retractable lanyard.

Seawater-resistant aluminum housing with retractable lanyard made of almost indestructible Dyneema® webbing.

Approved for vertical and horizontal use.

Edge tested: Tested at sharp edges, R ≥ 0,5 mm (CNB/P/11.060 2008 sharp edge Type A)
Carabiner: IKV 32 with opening width 66 mm in the bottom
Shock absorbtion: Max. shock impact < 4 kN.

... *Read more*

Material: Housing: aluminium, webbing: Dyneema®
Marking: According to standard
Temperature range: -40ºC up to +50ºC
Finish: Blue painted
Standard: EN 360


CERTEX Danmark A/S
info@certex.dk
+45 74 54 14 37

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Fall Arrest Block IKAR Flexible HWB 2,0 DWX

Blueprint



Technical data

Part code	Code	Max. number of persons	Length m	Max load kg	B mm	L mm	T mm	Weight kg
822100250660	HWB 2,0 DW X	1	2.5	136	170	425	67	2.2

CERTEX Danmark A/S
info@certex.dk
+45 74 54 14 37

© November 2026 - All Rights Reserved