



Round Sling Extreema® XS

Product information

The Extreema® XS sling is a compact high-strength round sling designed for lifting operations in confined or restricted spaces. It is used where traditional slings are too bulky or require larger hardware. Manufactured from HMPE, it combines high load capacity with a small diameter, enabling efficient and controlled lifting in tight environments.

WLL range: 3 – 20t

EWL range: 0,5m – 16m, (15t/20t can be made up to 65m)

When to choose this product

Best for:

- Lifting in confined spaces with limited clearance
- Applications requiring compatibility with standard shackles

Product benefits

- Compact diameter enables lifting in restricted or hard-to-reach areas
- D:d ratio 1:1 allows use with standard bow shackles
- HMPE construction provides high strength with low weight
- Lightweight design simplifies transport, handling, and storage
- Seamless sleeve supports durability and extended service life

Material: HMPE

Marking: According to standard, CE-marked

Temperature range: -40°C up to +70°C

Standard: EN 1492-2

except material

Safety factor: 7:1

Part code	WLL ton	EWL m	Colour	Delivery time
340500300050030	3	0.5	Yellow	10

340500300080030	3	0.75	Yellow	10
340500300100030	3	1	Yellow	10
340500300150030	3	1.5	Yellow	10
340500300200030	3	2	Yellow	10
340500300250030	3	2.5	Yellow	10
340500300300030	3	3	Yellow	10
340500300400030	3	4	Yellow	10
340500300500030	3	5	Yellow	10
340500300380030	3	3.75	Yellow	10
340500300700030	3	7	Yellow	10
340500300800030	3	8	Yellow	10
340500500050030	5	0.5	Red	2
340500500100030	5	1	Red	10
340500500150030	5	1.5	Red	10
340500500200030	5	2	Red	10
340500500250030	5	2.5	Red	10
340500500300030	5	3	Red	10
340500500400030	5	4	Red	10
340500500500030	5	5	Red	10
340500500080030	5	0.75	Red	10
340500500600030	5	6	Red	10
340500500700030	5	7	Red	10
340500500800030	5	8	Red	10

340501000150030	10	1.5	Orange	10
340501000200030	10	2	Orange	10
340501000300030	10	3	Orange	10
340501000400030	10	4	Orange	2
340501000500030	10	5	Orange	10
340501000100030	10	1	Orange	2
340501001250030	10	12.5	Orange	10
340501000800030	10	8	Orange	10
340501000600030	10	6	Orange	10
340501000050030	10	0.5	Orange	10
340501000700030	10	7	Orange	10
340501500400030	15	4	Orange	10
340502000000030	20	-	Orange	10
340502000600030	20	6	Orange	10

Technical data

Extreema® XS roundsling**HMPE EXS**

WLL	SF	Core ø mm	Weight kg 3m EWL	p/m extra kg
3t	7	9	0,8	0,25
5t	7	14	1,35	0,43
10t	7	23	2	0,65
15t	7	31	3,5	1,15
20t	7	37	4,6	1,50