



## **Round Sling EXTREEMA® XS**

## Product information

The XS round slings are the ultimate solution for lifting loads ranging from 1T to 20T. They offer a cost-effective and reliable alternative to traditional polyester slings. Say goodbye to the hassle of disposal, storage, and transportation costs, and welcome a practical and efficient choice that never compromises safety and quality.

Their lightweight design ensures easy handling and transport, making them a practical choice across various lifting applications. By embracing the XS round slings, industries secure a dependable lifting solution and embark on a sustainable journey, reducing industrial waste and minimizing their environmental footprint.

Extreema XS Slings have massive lifting power in a much smaller size with 78% less weight than polyester round slings and 55% smaller diameter, you can lift on the shackle pin. Slings are 8-10 times lighter than steel wire ropes.

## Features and benefits:

- Saving costs
- D:d ratio of 1:1
- Environmentally friendly
- Light in weight
- Flexible
- Less storage
- Long life cycle
- Access to limited lifting space
- Safer lifting operations
- Improving workflow
- Available in 3t yellow, 5t red, 10t orange, 15t orange and 20t orange
- Available in effective working lengths in the range of 0.5 m up to 16 m
- Standard with RFID

Material: HMPE -Dyneema® Marking: According to standard, CE-marked Temperature range: -50°C up to +70°C Standard: EN 1492-2 except material

Safety factor: 7:1

| Part code       | WLL<br>ton | EWL<br>m | Colour | Delivery time |
|-----------------|------------|----------|--------|---------------|
| 340500300050030 | 3          | 0.5      | Yellow | 10            |
| 340500300080030 | 3          | 0.75     | Yellow | 10            |
| 340500300100030 | 3          | 1        | Yellow | 10            |
| 340500300150030 | 3          | 1.5      | Yellow | 10            |
| 340500300200030 | 3          | 2        | Yellow | 10            |
| 340500300250030 | 3          | 2.5      | Yellow | 10            |
| 34050030030030  | 3          | 3        | Yellow | 10            |
| 340500300400030 | 3          | 4        | Yellow | 10            |
| 340500300500030 | 3          | 5        | Yellow | 10            |
| 340500500050030 | 5          | 0.5      | Red    | 10            |
| 340500500100030 | 5          | 1        | Red    | 10            |
| 340500500150030 | 5          | 1.5      | Red    | 10            |
| 340500500200030 | 5          | 2        | Red    | 10            |
| 340500500250030 | 5          | 2.5      | Red    | 10            |
| 340500500300030 | 5          | 3        | Red    | 10            |
| 340500500400030 | 5          | 4        | Red    | 10            |
| 340500500030    | 5          | 5        | Red    | 2             |
| 340501000150030 | 10         | 1.5      | Orange | 10            |
| 340501000200030 | 10         | 2        | Orange | 10            |
| 340501000300030 | 10         | 3        | Orange | 10            |
| 340501000400030 | 10         | 4        | Orange | 2             |
| 340501000500030 | 10         | 5        | Orange | 10            |

**Technical data** 

|     |    | Extreema® XS roundsling |                  |              |  |  |  |
|-----|----|-------------------------|------------------|--------------|--|--|--|
|     |    | HMPE EXS                |                  |              |  |  |  |
| WLL | SF | Core ø mm               | Weight kg 3m EWL | p/m extra kg |  |  |  |
| 3t  | 7  | 9                       | 0,8              | 0,25         |  |  |  |
| 5t  | 7  | 14                      | 1,35             | 0,43         |  |  |  |
| 10t | 7  | 23                      | 2                | 0,65         |  |  |  |
| 15t | 7  | 31                      | 3,5              | 1,15         |  |  |  |
| 20t | 7  | 37                      | 4,6              | 1,50         |  |  |  |