# Lubricant ROPETEX traction lube 40

**Product information**




Ropetex Traction Lube 40 is a synthetic lubricant which coats wire surfaces with a slip-resistant film. It is designed for situations in which frictional grip is vital, because it provides internal lubrication whilst avoiding excessive build-up with repeated applications.

**Typical applications:** Lifts, elevators and traction hoists.

**Application methods:** Portable sprayer or brushing/dripping.
**Minimum application temperature:** -5°C (product should be kept to at least 10°C for 48 hours before application).
**Color/texture:** White water fluid.
**NLGI Grade:** Solvent liquid
**4-ball weld load:** > 110 kgf

Available in a 20 liter drum.

**Extra:**
Do not forget to download the white paper with a lot of useful information about wire rope lubricants. It is free! (see the 'documents' tab).

... *Read more*

**Temperature range:** -55°C up to +40°C

**CERTEX Danmark A/S**
info@certex.dk
+45 74 54 14 37

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

# Lubricant ROPETEX traction lube 40

## Technical data

| Part code | Description |
|---|---|
| 142502000020 | Ropetex Traction Lube 40, 20 lit drum |

**CERTEX Danmark A/S**
info@certex.dk
+45 74 54 14 37

© November 2026 - All Rights Reserved