



## Lubricant ROPETEX ultra lube 2

### Product information

#### **ROPETEX**

Ropetex Ultra Lube 2 is an ecofriendly, advanced high-performance hybrid grease. It is developed to perform in dockside, offshore and deep-water environments. Furthermore, it has superior wash-off performance and is bio-degradable, non-toxic and non-bio accumulative.

Ropetex Ultra Lube 2 is an **Environmentally Acceptable Lubricant (EAL)** and is fully **VGP 2013** compliant. It can therefore be used on docksides, riversides, lakes and other environmental sensitive locations.

Due to the composition of the product, it is stable over a wide temperature range, making it suitable for tropical environments.

**Typical applications:** Offshore cranes, dockside cranes; offshore and harbor installations; subsea installations.

**Application methods:** High pressure equipment or brushing.

**Minimum application temperature:** -5°C (Product should be kept to at least 10°C for 48 hours before application).

**Color/texture:** Matte black grease

**NLGI grade:** 2

**Drop point:** 154°C

**Break point:** -60°C

**Relative density:** 0.9 - 0.95

**Hot salt spray test:** 2880 hours

**4-ball weld load:** > 400 kgf

**4-ball weld scar:** 0,55 mm

**Water spray-off:** < 60% retention

**Environmentally Acceptable Lubricant:** YES

**VGP 2013 compliant:** YES

Available in 12,5 kg pail.

#### **Extra:**

Do not forget to download the white paper with a lot of useful information about wire rope lubricants. It is free! (see the 'documents' tab).

**Temperature range:** -40°C up to +120°C

Part code	Description	Weight kg	Delivery time
-----------	-------------	--------------	---------------

142501250050

Ropetex Ultra Lube 2

12.5

10