



Trailer Winch

Product information



Trailer winches are robust and light, which makes them suitable for various applications such as: trailers, yachts, doors, wells, etc.

The winches are TUFFPLATE corrosion finished (3 times the corrosion resistance of standard zinc plating).

The brake range (not manual range) can be used for lifting but not for moving people or loads over where people would be. The braked winches are certificated that they compile with a TGV test to EN13157: + A1:2009 "Cranes and safety – Hand Powered lifting equipment".

Note: Excl. wire (to be ordered separately).

Part code	Code	WLL ton	Model	Rope Ø mm	Base dimensions mm	Lift/crank turn (mm)	Gear ratio	Length handle mm	Rope capacity m	Delivery time
501302720000410	02812	0.272	DL600A	4	100x90	16	3,2:1	178	19,2	10
501300040000410	08053	0.36	DLB800AG	4	100x100	48	4,4:1	178	23	10
501304080000410	02796	0.408	DL900A	5	100x90	16	3,2:1	178	10,9	10
501304990000410	02797	0.499	DL1100A	5	130x90	22	3,7:1	178	22,2	10
501305450000410	08054	0.545	DLB1200AG	5	130x100	54	5,4:1	238	19,4	10
501306350000410	07771	0.635	Caravan	4	130x100	22	4,4:1	241	33	10
501300070000410	08055	0.68	DLB1500AG	6	140x120	64	5,4:1	305	15,1	10
501308170000410	02799	0.817	DL1800A	7	140x120	28	10,3:1/5,4:1	241	17,9	10
501308170000414	02819	0.817	DL1802A	7	140x120	28	5,4:1	241	17,9	10
501309050000410	08059	0.905	DLB2000AG	7	180x120	64	17,3:1	238	8,9	10
501309070000410	02820	0.907	DL2000A	7	160x120	28	12,4:1/5,4:1	241	17,9	10
501311340000410	02810	1.134	DL2500AB	8	180x120	28	17,3:1/5,4:1	241	14,2	10
501311340000414	02821	1.134	DL2500A	8	180x120	28	17,3:1/5,4:1	241	14,2	10
501315890000410	06562	1.589	DL3500B	9	220x140	33	12:1/6:1	241	12,3	10