



## Baby Winch CWS-160, CWS-230

### Product information

Electrical winch with remote control for loads up to 230 kg.

- Lightweight and compact design: Allows easy installation.
- Upper hoisting limit switch: When rope disc touches the limit arm, hoisting is automatically stopped.
- Lower hoisting limit switch: Sensor arm automatically stops motor if the wire rope is under-wound.
- Mechanical ratchet brake: Double ratchet pawls brake provide instant and safe braking.
- Can operate on standard domestic power supply.
- Wire rope comes with a safety-latch weight hook.
- Emergency stop function switch is available upon request.

**Power supply:** 220V-240V x 1ph AC.

**Braking methods:** For motor: Electromagnetic, for gear: Double mechanical ratchets.

**Remote control:** Switch cord 10 m.

**Option accessory:** Crane CRH-0710.

Part code	Code	Diameter mm	WLL ton	Lifting height m	Lifting speed first layer m/min.	Lifting speed m/min Top layer	Weight kg	Delivery time
5406CWS160	CWS-160	4.8	0.16	30	22	15	22.5	10
5406CWS230	CWS-230	5	0.23	24	14	9	23	10

## Technical data

Code	Motor rating
CWS-160	IP44
CWS-230	IP44

## Blueprint

