Lifting Solutions Group
Axel Johnson International

Weighing Hook Dynascale

Product information



Featuring an integrated display, the Dynascale series of weighing hook provides great visibility, with an accuracy of 0.5%. Available with two shackles as standard, or with hook on option.

Specifications:

- Capacity range from 1t up to 12.5t
- LCD display of 5-digit of 30mm height
- 0.5% accuracy of full scale
- Automatic stop set at 20 min (can be delete in option)
- Multiple integrated functions (ON, Tare, Peak Hold, Units change)
- Units (kg, lbs, daN)
- IP54
- Replaces the previous MWX in our range

Functionalities:

- The Dynascale is a complete autonomous digital crane scale with integrated functions:
- On/Off
- Tare
- Peak hold
- Units change (kg, daN, lbs)
- Automatic zeroing
- Automatic stop without load or variation (20 min). Removal of automatic stop available as option
- Infrared remote control (Off, Tare, Peak hold, Units change)

... *Read more*

Material: Steel, aluminium
Temperature range: -20°C up to +50°C
Note: Minimum load 10% of WLL

Safety factor: 4:1


CERTEX Danmark A/S
info@certex.dk
+45 74 54 14 37

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Weighing Hook Dynascale

Blueprint



Technical data

Part code	WLL ton	Model	A mm	B2 mm mm	C2 mm mm	D mm	E mm	F mm	Weight kg
423500100390	1	Dynascale 1t	189.6	317	16.5	43	23	111.5	2.2
423500320390	3.2	Dynascale 3.2t	189.6	317	16.5	43	23	111.5	2.2
423500650390	6.5	Dynascale 6.5t	228.7	409	22	80	32	138	3
423501250390	12.5	Dynascale 12.5t	277.2	567.5	34.5	80	51	193.5	3.8

Model	Dynascale 1t	Dynascale 3.2t	Dynascale 6.5t	Dynascale 12.5t
IP Protection	IP 54			
Precision	+/- 0.5% at 21°C full scale			
Precision	+/- 5 kg	+/- 16 kg	+/- 32.5 kg	+/- 62.5 kg
Sample rate	3 Hz – 32 Hz in “Peak Hold Mode”			
Resolution	1 kg	2 kg	5 kg	10 kg
Units	kg / daN / lbs			
Battery life	50 h			

CERTEX Danmark A/S
info@certex.dk
+45 74 54 14 37

© November 2026 - All Rights Reserved