Lifting Solutions Group
Axel Johnson International

Wire Pulley Sheave, type BR

Product information

Pulley sheaves for rope deflection with plain bearing, with honed steel axle. Grooved profile turned to DIN 15061.

... *Read more*




Material: Sheave: S355J2. Mounting plate: gray cast iron GG20.
Finish: Wire rope sheave: galvanized, mounting plate: painted.
Note: Also available with ball-bearing, for higher load.

CERTEX Danmark A/S
info@certex.dk
+45 74 54 14 37

© November 2026 - All Rights Reserved

Wire Pulley Sheave, type BR

Blueprint



Technical data

Part code	Rope Ø range mm	Type	Max load ton	D1 mm	D2 mm	R mm	A x B mm	C mm	E x F mm	H mm	øL mm	Weight kg
140100600130	2-6	BR 050 G	0.3	50	38	3,2	67 x 67	7	50 X 50	35	7	0.6
140100800130	3-8	BR 075 G	0.6	75	59	4,2	75 x 75	10	60 X 60	50	9	1.4
140100900130	4-9	BR 100 G	0.9	100	80	4,8	90 x 90	10	70 X 70	65	12	2.5
140101000130	6-10	BR 125 G	1.1	125	103	5,3	92 x 92	10	70 X 70	75	12	3.2
140101200130	8-12	BR 150 G	1.25	150	126	6,5	12 x 100	12	75 X 90	90	14	4.8

CERTEX Danmark A/S
info@certex.dk
+45 74 54 14 37

© November 2026 - All Rights Reserved