Lifting Solutions Group
Axel Johnson International

Wire Pulley Block, type SB

Product information

Pulley sheaves for rope deflection with plain bearing, with honed steel axle. Grooved profile turned to DIN 15061.

... *Read more*



Material: S355J2.
Finish: Galvanized.
Note: Also available with ball-bearing, for higher load.


CERTEX Danmark A/S
info@certex.dk
+45 74 54 14 37

© November 2026 - All Rights Reserved

CERTEX | Lifting Solutions Group
Axel Johnson International

Wire Pulley Block, type SB

Blueprint



Technical data

Part code	Rope Ø range mm	Type	Max load ton	D1 mm	D2 mm	R mm	A/B mm	C mm	E / (F) mm	H1 mm	H2 mm	øL mm	Weight kg
140100600140	2-6	SB 050 G	0.05	50	38	3,2	115 / 95	7	30 / -	21,5	35	9	0.5
140100800140	3-8	SB 075 B	0.1	75	59	4,2	140 / 120	10	30 / -	25	41	11	0.9
140100900140	4-9	SB 100 G	0.15	100	80	4,8	175 / 145	10	40 / -	26,5	45	11	1.3
140101000140	6-10	SB 125 G	0.25	125	103	5,3	200 / 170	10	60 / 30	28,5	48	11	2.5
140101200140	8-12	SB 150 G	0.5	150	126	6,5	230 / 200	12	60 / 30	28,5	48	11	3.3

CERTEX Danmark A/S
info@certex.dk
+45 74 54 14 37

© November 2026 - All Rights Reserved