

Wedge Socket for Lifts



Product information

Symmetrical Wedge Socket for stranded steel wire ropes according to EN 12385-5 for lifts.

Marking: According to standard

Temperature range: -20°C up to +100°C

Finish: Galvanized

Standard: EN 13411-7

DIN 15315 replaced by EN 13411-7

Warning: Tensile strength should not exceed 1770 N/mm²

| Part code | Rope Ø range mm | Finish | B1mm mm | B2mm mm | B3mm mm | C mm | D, mm | E mm | H1mm mm | H2mm mm | H3mm mm | Rmm mm | S mm | Weight kg | Delivery time |
|--------------|-----------------|------------|---------|---------|---------|------|-------|------|---------|---------|---------|--------|------|-----------|---------------|
| 121500800072 | 6-8 | Galvanized | 12 | 14 | 11 | 37 | 12 | 20 | 150 | 75 | 92 | 12,5 | 4 | 0.57 | 10 |
| 121501100072 | 9-11 | Galvanized | 15 | 17 | 14 | 48 | 16 | 26 | 190 | 95 | 117 | 16 | 6 | 1.05 | 10 |
| 121501400072 | 12-14 | Galvanized | 20 | 22 | 18 | 58 | 18 | 32 | 230 | 115 | 141 | 19 | 8 | 1.89 | 10 |
| 121501700072 | 15-17 | Galvanized | 23 | 25 | 21 | 70 | 22 | 36 | 260 | 130 | 162 | 23 | 10 | 3.26 | 10 |

Blueprint

