

## Rigging Screw, Fork/Eye No. 402

---

### Product information

For tensioning of ropes, cables and the like.

Certificate: M20 – 2" can be delivered with certificate on request

... [Read more](#)

---

**Finish:** Hot dip galvanized.

**Note:** We only make certificates for the rigging screws which are individual tested and numbered.

**Warning:** M6 - M16 is NOT FOR LIFTING

**Safety factor:** 5:1



## Rigging Screw, Fork/Eye No. 402

### Blueprint



### Technical data

Part code	WLL ton	Thread mm	Tensioning length	B mm	F mm	G, mm	H, mm	K mm	L mm	Mmm mm	Nmm mm	Weight kg
4221A402410	0.5	M10	90	145	7	13	13	9.5	8	20	225	0.3
4221A402412	0.7	M12	155	195	10	14	28	13	10	30	315	0.65
4221A402416	1.2	M16	185	230	12	18	45	18	12	44	380	1.25
422100150370	1.5	M20	210	270	13	21	45	20	16	50	450	2.2
422100220370	2.2	M22	230	295	16	24	50	25	20	60	500	3.3
422100320370	3.2	M24	250	325	19	28	56	28	22	65	555	4.6
422100480370	4.8	1.1/4"	290	370	22	35	70	38	28	85	680	8.5
422100600370	6	1.1/2"	300	400	25	40	90	45	32	100	760	14.5
422100850370	8.5	1.3/4"	290	400	30	45	90	50	38	105	760	20.9
422101100370	11	2"	290	400	35	45	100	58	45	120	820	24