

## Rigging Screw, Eye/Eye No. 404

### Product information



Rigging screw for tensioning of ropes, cables and the like.

M10 – 2" can be delivered with certificate on request

**Finish:** Hot dip galvanized.

**Note:** We only make certificates for the rigging screws which are individual tested and numbered.

**Safety factor:** 5:1

Part code	WLL ton	Thread mm	Tensioning length	B,	F,	G,	H,	K,	L	M mm	N mm	Weight kg	Delivery time
422100050380	0.5	M 10	90	145	7	13	13	9.5	8	20	225	0.3	10
422100070380	0.7	M 12	155	195	10	14	28	13	10	30	315	0.65	10
422100120380	1.2	M 16	185	230	12	18	45	18	12	44	380	1.25	10
422100150380	1.5	M 20	210	270	13	21	45	20	16	50	450	2.2	10
422100220380	2.2	M 22	230	295	16	24	50	25	20	60	500	3.3	10
422100320380	3.2	M 24	250	325	19	28	56	28	22	65	555	4.6	10
422100480380	4.8	1-1/4"	290	370	22	35	70	38	28	85	680	8.5	10
422100600380	6	1-1/2"	300	400	25	40	90	45	32	100	760	14.5	10
422100850380	8.5	1-3/4"	290	400	30	45	90	50	38	105	760	20.9	10
422101100380	11	2"	290	400	35	45	100	58	45	120	820	24	10

## Blueprint

