Rigging Screw, Eye/Eye No. 404

Product information

Rigging screw for tensioning of ropes, cables and the like.

M10 – 2” can be delivered with certificate on request

... *Read more*



Finish: Hot dip galvanized.
Note: We only make certificates for the rigging screws which are individual tested and numbered.

Safety factor: 5:1


CERTEX Danmark A/S
info@certex.dk
+45 74 54 14 37

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Rigging Screw, Eye/Eye No. 404

Blueprint



Technical data

Part code	WLL ton	Thread mm	Tensioning length	B mm	F mm	G mm	H mm	K mm	L mm	M mm	N mm	Weight kg
422100220380	2.2	M 22	230	295	16	24	50	25	20	60	500	3.3
422100320380	3.2	M 24	250	325	19	28	56	28	22	65	555	4.6
422100480380	4.8	1-1/4"	290	370	22	35	70	38	28	85	680	8.5
422100600380	6	1-1/2"	300	400	25	40	90	45	32	100	760	14.5
422100850380	8.5	1-3/4"	290	400	30	45	90	50	38	105	760	20.9
422101100380	11	2"	290	400	35	45	100	58	45	120	820	24

CERTEX Danmark A/S
info@certex.dk
+45 74 54 14 37

© November 2026 - All Rights Reserved