

Rigging Screw stainless Jaw/Terminal

Product information

Stainless steel rigging screws design: fork / terminal a.k.a jaw / terminal.
Also available with other end fittings on request. The larger size rigging screws from M20 and up are designed with a rounded fork head and are available with Stainless Steel with bronze threaded inserts for smooth adjustment.

... [Read more](#)



Material: Stainless steel AISI 316.

Marking: Thread and/or wire size


Temperature range: -50°C to +100°C and briefly up to +200°C

Finish: Polished.

Warning: It is strongly recommended to lubricate threads first, before tensioning.

Rigging Screw stainless Jaw/Terminal

Blueprint



Technical data

Part code	Rope Ø range mm	Pin diameter mm	Size	Packing Qty.	PIN mm	A mm	B mm	D mm	L1 mm	L2 mm	Weight kg/100pc	Packing Qty.
1207120306	3	5	M6	10	5	7.5	9.4	6.35	232	170	8.5	10
1207120508	5	6	M8	10	6	9.5	13	9	281	205	13.2	10
1207120510	5	8	M10	10	8	11	14	9	312	228	22.5	10
1207120610	6	8	M10	10	8	11	17	12.6	328	248	25.6	10
1207120612	6	12	M12	5	12	14	14	12.58	393	287	47.5	5
1207120714	7	12	M14	5	12	14	25	14.2	439	319	58	5
1207120812	8	12	M12	5	12	14	25	16	416	310	53.5	5
1207120816	8	14	M16	5	14	18	32	16	498	365	89.5	5
1207121016	10	14	M16	5	14	18	33	17.8	506	373	93	5
1207121016L	10	14	M16	5	14	22	33	17.8	504	371	93	5
1207121020	10	19	M20	Bulk	19	24	48	17.8	587	427	170.1	-