

## Container Lifting Beam Type A and B



### Product information



Lifting beam for handling standard 20-ft and 40-ft containers. Delivered complete with wire rope slings or chain slings and Type CH or MK5 container hooks for attachment to container bottom fixings.

**Design:** Type A is a transverse beam with a low lifting height designed for lifting by the bottom fixings (as shown). Type B picture is a transverse beam in the form of a spreader. This requires a greater lifting height but offers superior balance and lighter weight.

**Proof:** 2 x WLL according to SS-EN 131 55

**Type A** Transverse beam

**Type B** Transverse beam - spreader picture.

**Material:** Hollow-beam and plate of high-strength structural steel.

**Marking:** Maximum load and CE mark.

**Finish:** Yellow painted.

**Note:** Manufactured in accordance with the Swedish and international standard SS-ISO 3874, which states that a lifting beam is required when handling loaded standard containers larger than 10 ft in

Part code	Code	WLL ton	Type	For container size (ft)	A mm	B mm	H mm	K mm	L	Weight kg	Delivery time
62056692A240	6692A-250	25	1C-1CC	20	350	160	680	3,700	2,500	550	10
62056694A360	6694A-360	36	1A-1AAA	40	500	220	880	6,100	2,500	800	10

### Technical data

# Blueprint

