Lifting Solutions Group
Axel Johnson International

Helicopter Beam X-Duplex

Product information



This type of lifting beam is designed as a folding crossbeam. The lifting beam is designed with one pullout per arm allowing the attachment points to be adjusted in the length/width. A 4-part sling must be used between the lifting beam and the crane hook. Other lengths and working loads can be manufactured upon request.
Design: Lightweight welded beam construction providing good torsional stiffness.
Proof load: 1,5 x WLL.

... *Read more*

Material: Beam and plate of high-strength structural steel.
Marking: Working load limit (WLL), CE marking, manufacturer, serial number, year of manufacturing, etc.
Finish: Yellow painted. Other treatments available on request.
Note: Top sling, separate slings and other accessories to be ordered separately.


CERTEX Danmark A/S
info@certex.dk
+45 74 54 14 37

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Helicopter Beam X-Duplex

Blueprint



Technical data

Part code	WLL ton	Type	L min. mm	L max. mm	L1 max. mm	Weight kg
62056502503400	2.5	Duplex 2.5	3,600	4,800	3,400	159
62056506003400	6	Duplex 6	3,700	4,800	3,400	199
62056510003400	10	Duplex 10	3,700	4,900	3,500	279
62056520003400	20	Duplex 20	3,700	4,900	3,500	492

CERTEX Danmark A/S
info@certex.dk
+45 74 54 14 37

© November 2026 - All Rights Reserved